
# **VISION MEASURING SYSTEM**









probe (optional), includes Ø2mm and Ø3mm styli, Ø25mm calibration ball, measuring accuracy is 10µm

lens with coaxial light (optional, must be mounted in factory)

#### **SPECIFICATION**

Code	ISD-V150	ISD-V250	ISD-V300
Measuring range (X×Y×Z)	150×100×200mm	250×150×200mm	300×200×200mm
Stage size	354×228mm	450×280mm	500×330mm
Stage glass size	210×160mm	306×196mm	350×250mm
Resolution of X/Y/Z axis	0.5μm		
Accuracy of X/Y axis	≤(2.5+L/100)µm (L is the measuring length in mm)		
Repeatability of X/Y axis	2μm		
Objective	0.7X ~ 4.5X (zoom)		
Working distance	92mm		
Magnification	33X ~ 195X (on 19" monitor)		
Camera	1/3" color CCD, 1.5M pixel		
Illumination	surface and contour with adjustable LED		
Max. height of workpiece	160mm		
Max. weight of workpiece	20kg		
Operation system	Windows 7		
Drive method	manual		
Power supply	110/220V, 50/60Hz		
Dimension(L×W×H)	560×540×850mm	760×600×900mm	760×600×900mm
Weight	100kg	120kg	140kg

## STANDARD DELIVERY

Main unit	1pc
Video card with dongle	1pc
Software disc	1pc
Calibration glass chart	1pc
Laser positioner	1pc
Clay	1pc
Foot switch	1pc
Anti-dust cover	1pc

#### **OPTIONAL ACCESSORY**

0.5X auxiliary objective	Code: ISD-V-OB05X Working distance: 175mm Magnification: 16.5 ~ 97.5X (on 19" monitor)
2X auxiliary objective	Code: ISD-V-OB02X Working distance: 36mm Magnification: 66 ~ 390X (on 19" monitor)
Probe	Code: ISD-V-PROBE Includes Ø2mm and Ø3mm styli, Ø25mm calibration ball
Lens with coaxial light	Code: ISD-V-LENS (must be mounted in factory)

## **SOFTWARE**

■ Operation system: Windows 7

■ Language: English

Single measuring tools:

measure coordinate of point

measure distance between two points

measure center coordinate and axis length of ellipse

measure length, width and diameter of key slot

measure length of open curve

measure focus distance of surface

measure angle of two lines

measure center coordinate, diameter and area of circle



measure length and diameter of arc



measure length, width and area of rectangle



measure width and diameter of ring




measure length and area of close curve




measure distance of two elements





measure distance and angle of two elements

#### Focus indicator:




#### Profile detection:



### Edge-detection:








### Coordinate transfer:






## ■ CAD measuring:




Input CAD drawing and set reference, then move the stage to make the target box in the center of crosshair, the software will do automatic measurement

## Contour scanning:



## ■ Data export to CAD, EXCEL and WORD



EXCEL

